

FIG. 1





FIG. 2

**FIG. 3**

## Pseudo Code for Translation Engine Control Module

```

100. INSTRUCT parameter table generator to create parameter table and initialize filter
101. INSTRUCT Synchronizer to initialize itself
102. INSTRUCT Synchronizer to LOAD the History File into its WORKSPACE
103. INSTRUCT R_Translator to LOAD R_records from R_Database
104. INSTRUCT L_Translator to SANITIZE R_records that were just LOADED
105. INSTRUCT L_Translator to LOAD L_Records from L_Database and SEND to Synchronizer
106. INSTRUCT R_Translator to SANITIZE L_Records that were just LOADED.
107. INSTRUCT Synchronizer to do CAAR (Conflict Analysis And Resolution) on all the records in
    WORKSPACE.
108. INFORM user exactly what steps Synchronizer proposes to take (i.e. Adding, Changing, and Deleting
    records). WAIT for User.
109. IF User inputs NO, then ABORT.
110. INSTRUCT R_Translator to UNLOAD all applicable records to R_Database.
111. INSTRUCT L_Translator to UNLOAD all applicable records to L_Database.
112. INSTRUCT Synchronizer to CREATE a new History File.

```

FIG. 4

# Pseudocode for Generating Parameter Table

```

{Get Input from the user}
150. ASK user to select whether to use a filter expression
151. IF the user selected to use a filter THEN
152.   IF a new filter to be used THEN
153.     Obtain from the user filter name
154.     Obtain filter expression
155.     STORE the current date and time in the FILTER_CHANGED_TIMESTAMP
        parameter
156.     Assign a unique filter ID to the filter
157.   ELSE Obtain from the user filter name
158.     retrieve the filter expression and unique filter ID
159.     IF user selects to edit the filter THEN display the filter and obtain edits
160.     SET FILTER_ID parameter to unique filter ID code of the selected filter
161.     SET USE_FILTER flag
162.     PARSE the filter expression into a filter token array
163.   END IF
164.   CREATE parameter table

```

**FIG. 5**





FIG. 6

**FIG. 7**

MS Schedule+ 7.0 filter - sched\_contacts\_2

Conditions Rules

Add a new filter condition to the list or Update the currently selected filter condition (highlighted in the list box below). Only items passing the conditions below will be transferred.

Field ▼ 66c

Last Name 66b

Operator: starts with ▼ 66d

Value: M

Add to List Remove Update

List of Filter Conditions: 66f

[Last Name] starts with 'M'

OK Cancel Help

66a 66 66g

FIG. 8



MS Schedule+ 7.0 filter - sched\_contacts\_2

Conditions Rules

64

64a

Select the rule for combining the conditions. You can either specify that all conditions must be met in order for an item to be transferred, or that at least one of the conditions must pass.

☒ All conditions must be met  
☐ One or more conditions must be met

List of Filter Conditions:

[Last Name] starts with 'M'

OK Cancel Help

FIG. 9

*Filter language specification*

*Expression* = *Condition1* [*AND Condition2*] ... [*OR Condition3*] ...

*Condition* = *ARG1 OP ARG2*

*OP* = *OP\_SET\_1* | *OP\_SET\_2* | *OP\_SET\_3* | *OP\_SET\_4* | *OP\_SET\_5* | *OP\_SET\_6*

*OP\_SET\_1* = *EQ* | *LE* | *GE* | *NE* | *LT* | *GT*

*OP\_SET\_2* = *OP\_SET\_1* *TODAY* - | *OP\_SET\_1* *TODAY* +

*OP\_SET\_3* = *OP\_SET\_1* *NOW* - | *OP\_SET\_1* *NOW* +

*OP\_SET\_4* = *STARTS\_WITH* | *CONTAINS* | *DOES\_NOT\_CONTAIN* | *IS\_EMPTY* | *IS\_NOT\_EMPTY*

*OP\_SET\_5* = + | - | \* | / | %

*OP\_SET\_6* = *IS*

*For Dates* - *ARG1 OP ARG2*:

[Date Fieldname]	<i>OP_SET_1</i>	'YYYYMMDD'   [Date Fieldname2]   <i>TODAY</i>
[Date Fieldname]	<i>OP_SET_2</i>	integer

*For Times* - *ARG1 OP ARG2*

[Time Fieldname]	<i>OP_SET_1</i>	'HHMM'   [Time Fieldname2]   <i>NOW</i>
[Time Fieldname]	<i>OP_SET_3</i>	integer

*For TextStrings* - *ARG1 OP ARG2*

[String Fieldname]	<i>OP_SET_1</i>	'textstring'   [String Fieldname2]
[String Fieldname]	<i>OP_SET_4</i>	'textstring'

*For Booleans* - *ARG1 OP ARG2*

[Boolean Fieldname]	<i>OP_SET_6</i>	<i>TRUE</i>
[Boolean Fieldname]	<i>OP_SET_6</i>	<i>FALSE</i>

*For Numbers* - *ARG1 OP ARG2*

[Number Fieldname]	<i>OP_SET_1</i>	integer   float
[Number Fieldname]	<i>OP_SET_5</i>	integer   float

FIG. 10

200. FOR each Record in history file  
201.     Load record  
202.     Write record to Workspace  
203.     Next

**FIG. 11**

```

300. IF Use_Filter = TRUE and R_Application_Is_Filtering = FALSE THEN
301.   _FOR each Record in the remote database
302.     Load record
303.     Filter the loaded record
304.     IF record passes the filter THEN mark as PASSED_FILTER
305.     ELSE mark as FAILED_FILTER
306.     Send record to synchronizer
307.     In Synchronizer: Write record to Workspace
308.   Next
309. ELSE IF Use_Filter = TRUE and R_Application_Is_Filtering = TRUE THEN
310.   Send the filter expression to R_Application
311.   Load filtered records
312.   IF the record passes current filter THEN Mark as PASSED_FILTER ELSE Mark as
     FAILED_FILTER
313.   Send records to synchronizer
314.   In Synchronizer: Write records to Workspace
315. END IF

```

FIG. 12

```

350. Form all records in the workspace into CIGs
351. For each CIG
352.   Compare the records in CIG
353.   Determine synchronization outcome
354.   IF a synchronization outcome is a conflict THEN
355.     IF one of the database records in the CIG does not pass the current filter, THEN skip CIG and
       mark results as DO NOT UPDATE any of the records
       ELSE resolve conflict by reference to a user-selected rule or input from the user
356.   END IF
357.   IF the most up to date record fails the filter, THEN mark all records as having failed the
       current filter
358.   IF the filter expressions contains an unmapped field and one of the database records in the CIG
       are marked as having failed the filter, THEN mark all records as having failed the filter
359.   IF a fanned out recurring record is partially outside of the current filter, THEN mark the
       record to be fanned when being unloaded and delete previous fanned nonrecurring records
360.
361. Next

```

FIG. 13

```

400.  FOR each remote database record
401.      IF Use_Filter = TRUE and the filter is a static filter THEN
402.          IF record is marked as FAILED_FILTER THEN
403.              Delete record on the remote database
404.              Else IF the record is marked as PASSED_FILTER THEN add, delete, or modify
                     record according to results of synchronization obtained during CAAR analysis
405.          ELSE IF Use_Filter = TRUE and the filter is a dynamic filter THEN
                     IF record fails the current filter THEN
406.                         Delete record on the remote database
407.                         Else IF the record passes the current filter THEN add, delete, or modify record
408.                             according to results of synchronization obtained during CAAR analysis
409.      END IF
410.  Next

```

FIG. 14

```

450. FOR each local database record
451.   IF Use_Filter = TRUE and the filter is a static filter THEN
452.     IF record is marked as FAILED_FILTER THEN
453.       IF CAAR outcome is to modify the record then modify the record on the
         local database
454.     Else IF the record is marked as PASSED_FILTER THEN add, delete, or modify
         record according to results of synchronization obtained during CAAR analysis
455.   ELSE IF Use_Filter = TRUE and the filter is a dynamic filter THEN
456.     IF record fails the current filter but marked as PASSED_FILTER THEN
457.       IF CAAR outcome is to modify the record then modify the record on the
         local database
458.   Else IF the record passes the current filter THEN add, delete, or modify record
         according to results of synchronization obtained during CAAR analysis
459.   END IF
460. Next

```

FIG. 15




FIG. 16